Sound Control Technologies

RCU2S-BA8™ USB Application Guide

Updated: 8/28/2023

The **RCU2S-BA8™** supports multiple camera models:

- Angekis Saber Plus
- AVer TR311HWV2
- AVer TR313V2
- AVer TR323NV2
- AVer TR333NV2
- ClearOne Unite 150
- ClearOne Unite 200
- Huddlecam HC10X-GY
- Huddlecam HC20X-GY/WH
- Huddlecam HC20X
- Huddlecam HC30X
- Lumens VC-B30U
- Marshall CV610-UB
- Minnray UV950A
- PTZ Optics 12X USB
- PTZ Optics 20X USB
- Sony SRG-120DU
- VDO360 Saber20X NDI
- VDO360 CompassX
- VHD V71U2
- VHD V20C
- VHD VX110
- VHD VX710N
- VHD VX701L
- VHD VX120

Shown: **ClearOne Unite 200**

3.5mm Audio Cable
Integrator-Supplied

RCC-C005-0.3M
RJ45 (RCU2S-CE™) Y Cable
to 4mm Power Barrel
to 8 Pin Mini Din

RCC-C006-0.4M*
RJ11 (RCU2S-CE™) to 8 Pin Mini Din

***Purchased Separately:**
Cable required for VISCA Loop or Daisy Chain Functionality. Do not connect to last camera in Daisy-Chain. This will terminate control on all cameras.

RCU2S-HE™ Front Panel
Field-Upgradeable microSD Slot

RCC-M004-1.0M
USB-B (RCU2S-HE™)
to USB-A

Laptop

RCU2S-HE™

RCU2S-CE™

SCTLink™ Cable
Power, Control & Video

The SCTLink™ cable must always be a single, point-to-point CAT cable with no couplers or interconnections.

SCTLink™ Cable Specs
Integrator-Supplied CAT5e/CAT6 STP/UTP Cable
T568A or T568B (100m Max Length)

RJ45 Pinout

RCC-M004-0.3M
USB-A (RCU2S-CE™)
to USB-B

WPS-12 30VDC
100-240V 47-63Hz
Power Supply

Module Dimensions
RCU2S-CE™: H: 0.789" (20mm) **x W:** 2.264" (57mm) **x D:** 3.725" (94mm)
RCU2S-HE™: H: 1.448" (36mm) **x W:** 3.814" (96mm) **x D:** 3.578" (90mm)